

# Advantages of DuPont™ Tyvek® IsoClean® Single-Use Controlled Environments Garments and Accessories

**DuPont Controlled Environments (CE) garments and accessories, designed for single use, offer meaningful advantages in today’s challenging cleanroom environments.**

**DuPont™ Tyvek® IsoClean® single-use garments provide a more consistent fabric barrier and strength than reusable garments because they are not subjected to multiple cycles of wearing, laundering and sterilization. DuPont CE garments can also help minimize cross-contamination risk because they are clean-processed and packed in a facility that handles only new garments.**

One method to sterilize cleanroom garments is exposure to gamma radiation. But this also affects the polymer that makes up the garment. This effect is cumulative, so every time a garment is exposed to gamma radiation, additional changes to the polymer can occur.

The effect of gamma radiation on polyester has been widely studied<sup>12</sup> and one typical reaction that occurs is known as chain scission. This means that “breaks” are created in the backbone of the polymer, shortening up the polymer molecule chains (see figure 1). These segments can also recombine and cross-link, linking together different polymer chains. With repeated exposure to gamma radiation, these changes can impact the performance of the polymer and garments.

To aid in your garment decision-making, DuPont is conducting a study to map the properties of polyester reusable garments compared to washing and gamma radiation exposure cycles.

For research, two different types of polyester woven garments typically worn in cleanrooms were purchased. They were laundered and exposed to gamma radiation in consecutive cycles. To expedite the study, the garments were not subjected to wear, only laundering and radiation exposure. The study plan calls for garments to be evaluated after set numbers of cycles. It also provides for testing of critical performance properties at third-party laboratories. Some initial results from this study are shared.

To establish the baseline performance of the reusable polyester garments, properties of the garments were measured “as received,” without any laundering or exposure to gamma radiation. Bacterial filtration efficiency (BFE) was measured consistent with method ASTM F2101. These baseline results are shown in Chart 1.

FIGURE 1

## Pictorial Description of the Effect of Gamma Radiation on Polymer Molecule Chains





CHART 1

## Average Bacterial Filtration Efficiency (%)

Higher numbers indicate better filtration efficiency




\*Results average of 10 measurements per fabric type from "as-received" garments

\*\*Results as reported in SafeSPEC™

For single-use garments, the impact of gamma radiation on the polymer only occurs one time, so the properties are consistent.

DuPont™ Tyvek® delivers an ideal balance of protection, durability and comfort.



DUPONT™ TYVEK® IS MADE WITH A UNIQUE FLASH-SPINNING PROCESS THAT CREATES A TORTUOUS PATH FOR PARTICLES.

IMAGE SHOWN AT 200X MAGNIFICATION.

**DuPont is in the process of completing the tests on reusable garments and on the polymer that makes up the garments. Expect to see more results as the study progresses.**

**For the most up-to-date information, consult SafeSPEC™ at [www.SafeSpecCleanroom.dupont.co.uk](http://www.SafeSpecCleanroom.dupont.co.uk)**

<sup>1</sup>Potnis, S. P., Shetty, S. M., Rao, K., N., and Prakash, J. "Studies in Effect of Gamma Radiation on Synthetic Fibres – I." *Die Angew. Makromol. Chem.* 6 (1969) 127-135.

<sup>2</sup>Nair, P. D., Sreenivasan, K., and Jayabalan, M. "Multiple Gamma Radiation Sterilization of Polyester Fibres." *Biomaterials*, 9 (1988) 335-338.

This information is based upon technical data that DuPont believes reliable. It is subject to revision as additional knowledge and experience are gained. DuPont makes no guarantee of results and assumes no obligation or liability in connection with this information. It is the user's responsibility to determine the level of toxicity and the proper personal protective equipment needed. The information set forth herein reflects laboratory performance of fabrics, not complete garments, under controlled conditions. It is intended for information use by persons having technical skill for evaluation under the specific end-use conditions, at their own discretion and risk.

Anyone intending to use this information should first verify that the garment selected is suitable for the intended use. In many cases, seams and closures may provide less barrier than the fabric. If the fabric becomes torn, abraded or punctured, end user should discontinue use of garment to avoid compromising the barrier protection. **SINCE CONDITIONS OF USE ARE OUTSIDE OUR CONTROL, WE MAKE NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING WITHOUT LIMITATION, NO WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE AND ASSUME NO LIABILITY IN CONNECTION WITH ANY USE OF THIS INFORMATION.** This information is not intended as a license to operate under or a recommendation to infringe any patent, trademark or technical information of DuPont or others covering any material or its use.

